

AMERI-SOURCE™

TECHNICAL INFORMATION

GRADE AS-UF MOLDED GRAPHITE

Ultra fine grain, high density, and excellent mechanical properties

Typical Applications

- Continuous Casting dies
- Hot Pressing Molds and Punches
- Composite Tooling
- EDM electrodes

Sizes Available

- Block 16" x 16" x 20" (Larger sizes available)
- Rounds 2"diameter through 16" diameter x 20" long

Typical Properties @ room temperature

	ENGLISH	AG	METRIC	AG	
Density	lbs/ft 3	110	g/cm 3	1.83	
Particle Size (max)	inches	0.003	mm	0.075	
Specific Resistance	10 4 Ω in	4.5	μΩm	10	
Flexural Strength	psi	5,800	Mpa	40	
Compressive Strength	psi	11,500	Mpa	80	
CTE (to 100 deg. C)	10-6/deg F	1.7	10-6/deg C	3.0	

This information is not to be taken either as a warranty or representation for which we assume legal responsibility nor as permission or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation and verification.

SOLUTIONS TO GLOBAL COMPETITION

Ameri-SourceTM Specialty Products 5372 Enterprise Blvd. Bethel Park, PA 15102-2532 Tel: (412) 831-9400

Fax: (412) 831-9401

www.ameri-source.com

